TopTech comfort | excellence

Product #

- **7D** 7-Day Programmable
- **5/1/1** 5/1/1 Programmable
- **5-2** 5-2 Programmable
- **NP** Non-Programmable

	Product #	Programmable	Stages of Heat	Stages of Cool	Gas, Electric or Oil	Heat Pump	Millivolt	Battery Powered	24V Power (Hardwire)	Dual Fuel Compatible	Display Size (Square Inches)	Auto Changeover	Filter Change Reminder	Room Temperature Calibration	Minimum Compressor Run Time	Compressor Short Cycle Delay	Adjustable Heating Temperature Swing	Adjustable Cooling Temperature Swing	Programmable Fan	Keypad Lockout	Lite Commercial Compatible	Adjustable Setpoint Limits	Averaging & Remote Sensor Capable	Humidity Control	Memory Type (permanent)	Touchscreen	Warranty (Years)	Terminals (Shielded cable not required)
TOUCHSCREEN	**Wireless**																											
TOUCHSCREEN	**TT-S-955WH****	7D 5/1/1 NP	3*	2	•	•		•	•	H	13	•	•	•	•	•	•	•	•	•		•	•	•	•	•	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, H, DH
TOUCHSCREEN	**Wired**																											
TOUCHSCREEN	**TT-S-955**	7D 5/1/1 NP	3*	2	•	•	•	•	•	S	13	•	•	•	•	•	•	•	•	•		•			•	•	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
LARGER	**TT-S-855C** Flex-Stat	7D 5/1/1 NP Occ UnOcc	3*	2	•	•	•	•	•	S	8	•	•	•	•	•	•	•	•	•	•	•			•		5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
LARGER	**TT-S-855**	7D 5/1/1 NP	3*	2	•	•	•	•	•	S	8	•	•	•	•	•	•	•	•	•		•			•		5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
LARGER	**TT-N-851**	NP	3*	2	•	•	•	•	•	S	8	•	•	•	•	•	•	•		•		•			•		5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
LARGER	**TT-N-801**	NP	1	1	•	•	•	•	•		8	•	•	•	•	•	•	•							•		5	Rh, Rc, C, Y, W, G, B, O
LARGE	**TT-S-755R**	5/1/1 NP	3*	2	•	•	•	•	•	H	6		•	•	•	•	•	•	•			•	•		•		5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
LARGE	**TT-S-755H**	5/1/1 NP	3*	2	•	•	•	•	•	S	6		•	•	•	•	•	•	•			•		•	•		5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, H, DH
LARGE	**TT-S-755**	5/1/1 NP	3*	2	•	•	•	•	•	S	6		•	•	•	•	•	•	•						•		5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
LARGE	**TT-N-751H**	NP	3*	2	•	•	•	•	•	S	6		•	•	•	•	•	•						•	•		5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, H, D
LARGE	**TT-N-751**	NP	3*	2	•	•	•	•	•	S	6		•	•	•	•	•	•							•		5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
LARGE	**TT-N-721**	NP	2	1		•		•	•	S	4		•	•	•	•	•	•							•		5	R, C, Y, W2, E, G, B, O
LARGE	**TT-P-705**	5/1/1	1	1	•	•	•	•	•		4		•	•	•	•	•	•							•		5	Rh, Rc, C, Y, W, G, B, O
LARGE	**TT-N-701**	NP	1	1	•	•	•	•	•		4			•		•	•	•							•		5	Rh, Rc, C, Y, W, G, B, O
WIRELESS	**TT-N-631W**	NP	2	1	•	•		•	•		2			•	•	•	•	•				•			•		5	R, C, Y, W, GL, GH, B/O
VALUE	**TT-P-411**	5-2	1	1	•		•	•	•					•		•	•	•				•			•		2	Rc, Rh, B, O, Y, W, G, C
VALUE	**TT-P-421**	5-2	2	1	•	•	•	•	•					•		•	•	•				•			•		2	R, O, B, C, Y1, E/W1, G, W2
VALUE	**TT-N-411**	NP	1	1	•		•	•	•					•		•	•	•				•			•		2	Rh, Rc, B, O, Y, W, G, C
VALUE	**TT-N-421**	NP	2	1	•	•	•	•	•					•		•	•	•				•			•		2	R, O, B, C, Y1, E/W1, G, W2
	TT-WCTO	Wireless Component Terminal Operator	3*	2	•	•			•																		5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, Input 1 & 2

Accessories

Wireless ** Sensors	Remote Indoor: **TT-RIS-251W**	Remote Outdoor: **TT-ROS-250W**	**Hardwired Sensors**	Remote indoor: **TT-RIS-251S** Remote Outdoor: **TT-ROS-250S**
Wireless ** Repeater	Part Number: **TT-W150W**		**BackPlate**	Part Number: **T119**

* **3** heat stages for heat pump or **2** heat stages for conventional.

Wireless accessories available for **TT-S-955WH.

H Dual fuel hardware balance point. Requires Outdoor Temperature Sensor accessory **TT-ROS-250W or TT-ROS-250S**

S Dual fuel software setting. **Y** de-energizes when **W2** energizes.